



MICHIGAN POWER CLEANING

MANUFACTURER OF POWER WASHERS
PARTS & SERVICE

2101 PALMER AVENUE • KALAMAZOO, MICHIGAN 49001
PHONE: (269) 349-3656 • (800) 654-0480 • FAX: (269) 349-3658



Choose 12v DC powered or 115v powered, Diesel heated

Hot Water Generator

The **Hot Water Generator** attaches to your existing cold water pressure washer to give you the power of hot water to quickly melt away grease and grime. The cold water pressure washer provides high pressure water into the Hot Link which heats the water before delivering it through the spray gun and wand. The Hot Link is flow controlled; when the gun is pulled, the burner automatically starts and stops when the gun is released. Simply attach the Hot Link to almost any cold water pressure washer using the included jumper hose, then connect the pressure washer's hose, gun/wand and nozzles to the outlet on the Hot Link.

HY-HB-12V

HY-HB-115V

PRESSURE	Connect to any cold water pressure washer up to 4350psi (300bar)	
FLOW CAPACITY	Use your existing pressure washer, up to 5 gpm	
	4gpm @ 100°F heat rise, up to 200°F	4.75gpm @ 100°F heat rise, up to 200°F
VOLTS / AMPS	12v DC - Connect to battery on pressure washer (requires 14amp charging system)	115v, 1ph, 2amp includes 37' GFCI cord
CONTROLS/SWITCHES	Adjustable thermostat, lighted on/off switch	
PRESSURE CONTROL	Safety features include flow switch, pressure relief valve and burst disc	
PRESSURE HOSE	Not included – your gun and hose must be rated for at least 200°F	
GUN / WAND	Not included – your gun and hose must be rated for at least 200°F	
JUMPER HOSE	Includes 48", 5000psi, 250°F hose to connect Hot Link to existing pressure washer	
BURNER COIL	1/2" sch. 80 steel pipe, cold rolled 4 spiral, ceramic insulation	
CONSTRUCTION	Rugged, powder coated base frame, stainless coil wrap, and double-wall coil end caps	
BURNER FUEL/CAP	Diesel #2, 4 gallon for burner	
	274,400 Btu input	325,000 Btu input
MOUNTING	4) Holes to bolt down to your truck or trailer	
WEIGHT/DIMENSIONS	180#, 29"l x 22"w x 22"h	

Specifications subject to change without notification and may vary due to ambient conditions.

Featuring:

- ✓ **Use with your existing cold water pressure washer:** you don't need to purchase a complete hot water unit when you already have a cold water pressure washer
- ✓ **Adjustable temperature up to 200°F** for those stubborn jobs such as grease, gum, or graffiti
- ✓ **Compact** size allows for easy storage when not in use and takes up less room on your truck or trailer





MICHIGAN POWER CLEANING

MANUFACTURER OF POWER WASHERS
PARTS & SERVICE

2101 PALMER AVENUE • KALAMAZOO, MICHIGAN 49001
PHONE: (269) 349-3656 • (800) 654-0480 • FAX: (269) 349-3658



NEW – Hot Water Generator

Attach to your existing cold water pressure washer and you have the power of Hot Water to quickly melt away grease and grime.

Features:

- Use with your cold water pressure washer
- 100 - 4350 psi
- 1-5 gpm
- Includes 48" jumper hose
- 4 gallon diesel fuel tank
- Adjustable temp up to 200°F
- Stainless steel insulated coil enclosure
- Redundant safety features include flow switch, pressure relief valve, and burst disc
- Compact: 29" x 22" x 22"
- 2 Models Available:
 - 12v DC for remote use, hook to the battery on your pressure washer (requires 14 amp charging system)
 - 115v includes 37' GFCI cord, plugs into any standard 15 amp outlet



Benefits:

The Hot Link System allows you the flexibility of using hot water on those stubborn jobs such as grease, gum, or graffiti that require the impact of hot water to get the job done right. It will save you money by getting the job done faster, and you do not have to buy a new pressure washer if you already have a cold water system. Its compact size allows for easy storage when not in use and takes up less room on your truck or trailer.

Model# HY-HB-12 – 12v DC powered, diesel fired

Model# HY-HB-115 – 115v powered, diesel fired

